



## AGRICULTURAL LINE

# TE/CP

## FLAIL MOWERS FOR GRASS, BUSHES AND BRANCHES

FOR MIDI-EXCAVATORS - NO DRAIN LINE REQUIRED



Flail mower head, for cutting grass, branches, bushes, dense vegetation, suitable to midi-excavators from 9,0 to 15,0 tons an power up to 120 hp. Max. cutting diameter 9 cm.



### STANDARD EQUIPMENT:

The mower head is delivered with a steel plate unpainted for welding the hitch excavator bracket. The hydraulic motor is the Fixed piston version with size of 47cc or 55cc. Every hydraulic motor is equipped with a by-pass (anticavitation) valve. Pre-setted at factory according to the size piston motor fitted on. Every piston motor can be used without the drain port connection, but it must specified at the order, if the excavator hasn't the drain line on it. Belt transmission with 3 XPB belts, rear adjustable roller, frontal protection with chains and rear protection with rubber.

### Technical information

Model	Code	Cutting wide cm. 	Exterior width cm. 	Weight kg. 	Excavator weigh ton. 	Flow rate lt/min 	Pressure set bar 
TE/CP 120	64125	125	145	490	8.0 - 12.0	85 - 100	230 - 250
TE/CP 160	64160	160	185	630	10.0 - 15.0	85 - 100	230 - 250

### Tools

	Heavy hammers for runners, bushes, reeds, Diam.max 8 cm. Cod. ZP 00002 Rotor G 10 -12 pcs		Knives for grasses, bushes, reeds max size 6 cm Cod. ZP 293020 Rotor F 10 - 12 kit (x4)
---	---	--	---

### Optional

Floating linkage	Oil flow divider 3/4"	Excavator hitch bracket	<b>DRAINLESS</b> piston motor version
------------------	-----------------------	-------------------------	---------------------------------------