



## FORESTRY LINE

# TTK

## MINI-FORESTRY MULCHER FOR SMALL TRACTORS, CAT. 1 E 2, FROM 30 TO 60 HP



<b>510 - 560 Kg</b>	<b>30 - 60 HP</b>	<b>Ø max 12 cm</b>
---------------------	-------------------	--------------------

Mini-Forestry mulcher, suitable on small tractors with Low pto position (40-45cm from the ground) equipped with fixed tooth rotor to mulch grass, branches, wood and dense vegetation up to 12cm diam. Tractor power required from 30 to 60 hp.

### STANDARD EQUIPMENT:

Three point linkage cat. I° and II°, Pto 540 rpm, rear hydraulic door, Stronger frame built with quality steel double chassis, and counter blades. 60 hp gear box with free wheel, rotor with K fixed tooth built tube 200mm diam and 12,5 tick., DCR bite limiter system on rotor, pto cardan shaft gr. 6 with shear bolt clutch, lateral skids with wear resistant steel, internal steel chassi in wear resistant steel, The pushing frame is included as standard equipment.

### Technical information

Model	Code	Cutting width cm.	Overall dim. cm.	HP tractor	Weight kg.	PTO	Belts nr.	Teeth nr.	Tube diam. mm	Rotor diam. mm
TTK 110	155110	110	130	30-50	510	540	3	39	200	350
TTK 130	155130	130	150	40-60	560	540	3	45	200	350

### Tools

<p>K1 plus tooth Fixed tools recommended for cutting grass and dense vegetation max 12 cm, code ZPK280</p>		 <p>Rotor with wear resistant steel profiles (DCR) for both types of tools.</p>
<p>K2 tooth Fixed tools recommended for dense vegetation in the presence of rocky ground max 12 cm. code ZPK278</p>		